

# SEKONIC®

## L-208



Specifications			SEKONIC L-208	
Light receivingment	Incident light	Swivel head	No	
		Lumidisc	No	
	Reflected light	Switching incident/reflected	No	
		Light receiving angle	33(Lumigrad)	
		Viewfinder(Optional)	No	
	Flash light	Multiple flash mode	No	
Cordless/cord-in mode		No		
Rado triggering		No		
Measuring Range(ISO100)	Ambient	Incident	EV	3 to 17
		Reflected	EV	3 to 17
		Illuminance	LUX	No
			FC(FootNoCandle)	No
		Luminance	Cd/m2	No
	FL(FootNoLambert)		No	
	Flash	Incident	F	No
		Reflected	F	No
Display	ISO Sensitivity		ISO	12 to 12,500
			ISO 2	No
	Ambient	Aperture	Digital	No
			Step	1/2AV
			Analog dot scale	No
		Shutter speed	Step	No
			Digital	No
	Cine speed	Step	No	
		Digital	No	
	Flash	Aperture	Digital	No
Shutter speed		Digital	No	
Setting Range	Film		ISO	No
			Step	No
			ISO 2	No
			Step	No
	Ambient	Aperture	F	No
			Step	No
		Shutter speed	T	No
	Step		No	
	Cine	frame per second	No	
		Flash	Shutter speed	T
Step	No			
Operation function			Multiple cumulative	No
			Average	No
			Flash Analyzing	No
			Memory	No
			Memory clear	No
			Battery check	Yes
			Auto power off	No
			Under/Over exposure display	No
			Exposure Warning Indicator	No
			Exposure compensation	No
			Calibration compensation	No
			Synchro terminal	No
			LCD backlight	No
			Water registance	No
			Switching incident/reflected	No
			Retractable lumisphere	No
			Running (setting) lock	No
			Set/change dial (jog wheel)	No
			Diopter adjustment	No
			Tripod socket	No