

SEKONIC®

L-308S



Specifications			SEKONIC L-308S		
Light receivgement	Incident light	Swivel head	No		
		Lumidisc	Removable		
	Reflected light	Switching incident/reflected	Slide		
		Light receiving angle	40(Lumigid)		
		Viewfinder(Optional)	No		
	Flash light	Multiple flash mode	Yes		
		Cordless/cord-in mode	Yes		
Rado triggering		No			
Measuring Range(ISO100)	Ambient	Incident	EV	- to 19.9	
		Reflected	EV	0 to 19.9	
		Illuminance	LUX	No	
			FC(FootNoCandle)	No	
			Luminance	Cd/m2	No
	Flash	Incident	F	F1.4 to F90_0.9	
		Reflected	F	F1.4 to F90_0.9	
Display	ISO Sensitivity		ISO	3 to 8,000	
			ISO 2	No	
	Ambient	Aperture	Digital	F0.5 to 90	
			Step	1AV	
				Analog dot scale	F0.5 to90
				Step	No
	Shutter speed	Digital		60m to 1/8000	
		Step		1TV	
	Cine speed	Digital		8 to 128f/s	
		Aperture		Digital	F0.5 to 90
Flash	Shutter speed		Digital	1s to 1/500	
Setting Range	Film		ISO	3 to 8,000	
			Step	1/3SV	
			ISO 2	No	
			Step	No	
	Ambient	Aperture	F	No	
			Step	No	
		Shutter speed	T		60s to 1/8000
	Step		1TV		
	Cine	frame per second		8,12,16,18,24,25,30,32,64,128	
		Flash	Shutter speed	T	1s to 1/500
Step	1TV				
Operation function			Multiple cumulative	No	
			Average	No	
			Flash Analyzing	No	
			Memory	No	
			Memory clear	No	
			Battery check	Yes	
			Auto power off	Yes	
			Under/Over exposure display	Yes	
			Exposure Warning Indicator	No	
			Exposure compensation	No	
			Calibration compensation	No	
			Synchro terminal	Yes	
			LCD backlight	No	
			Water registance	No	
			Switching incident/reflected	Yes	
			Retractable lumisphere	No	
			Running (setting) lock	No	
			Set/change dial (jog wheel)	No	
			Diopter adjustment	No	
			Tripod socket	No	