

SEKONIC®

L-358



| Specifications | | | | SEKONIC L-358 |
|-------------------------|-----------------|---------------|------------------------------|--|
| Light receivingement | Incident light | | Swivel head | Horizontal (270 degrees) |
| | | | Lumidisc | Retractable |
| | Reflected light | | Switching incident/reflected | Removable |
| | | | Light receiving angle | 54(Lumigrad) |
| | | | Viewfinder(Optional) | VF1, 5, 10° |
| | Flash light | | Multiple flash mode | Yes |
| | | | Cordless/cord-in mode | Yes |
| Rado triggering | | | Yes (Optional) | |
| Measuring Range(ISO100) | Ambient | Incident | EV | -2 to 22.9 |
| | | Reflected | EV | 1 to 24.4(54 degrees) |
| | | Illuminance | LUX | No |
| | | | FC(FootNoCandle) | No |
| | | Luminance | Cd/m2 | No |
| | | | FL(FootNoLambert) | No |
| | Flash | Incident | F | F1.0 to F90.9 |
| | | Reflected | F | F1.0 to F90.9 |
| Display | ISO Sensitivity | | ISO | 3 to 8,000 |
| | | | ISO 2 | 3 to 8,000 |
| | Ambient | Aperture | Digital | F1.0 to 90 |
| | | | Step | 1, 1/2, 1/3 AV |
| | | | Analog dot scale | F1.0 to 90 |
| | | Shutter speed | Step | 1/2AV |
| | | | Digital | 30m to 1/8000 |
| | | | Step | 1, 1/2, 1/3 AV |
| | Cine speed | Digital | 2 to 360f/s | |
| | Flash | Aperture | Digital | F1.0 to 90.9 |
| Shutter speed | | Digital | 30m to 1/1000 | |
| Setting Range | Film | | ISO | 3 to 8,000 |
| | | | Step | 1/3SV |
| | | | ISO 2 | 3 to 8000 |
| | | | Step | 1/3SV |
| | Ambient | Aperture | F | F1.0 to 90 |
| | | | Step | 1, 1/2, 1/3 AV |
| | | Shutter speed | T | 30m to 1/8000, 1/200,1/400 |
| | | | Step | 1, 1/2, 1/3 AV |
| | | Cine | frame per second | 2,3,4,6,8,12,16,18,24,25,30, 32,36,40,48,50,60,64,72,75 , 90,96,120,128,150,200,240 |
| | | | Shutter speed | T |
| | Flash | Shutter speed | Step | 1, 1/2, 1/3 AV |
| | | | | |
| Operation function | | | Multiple cumulative | Yes(unlimited) |
| | | | Average | Yes |
| | | | Flash Analyzing | Yes(in 10% increments) |
| | | | Memory | Yes(9 memory banks) |
| | | | Memory clear | Yes(MODE + ISO2) |
| | | | Battery check | Yes |
| | | | Auto power off | Yes(20 min.) |
| | | | Under/Over exposure display | Yes |
| | | | Exposure Warning Indicator | No |
| | | | Exposure compensation | Yes(No9.9 to +9.9) |
| | | | Calibration compensation | Yes(No1.0 to +1.0) |
| | | | Synchro terminal | Yes |
| | | | LCD backlight | Yes |
| | | | Water registance | Yes |
| | | | Switching incident/reflected | No |
| | | | Retractable lumisphere | Yes |
| | | | Running (setting) lock | Yes |
| | | | Set/change dial (jog wheel) | Yes |
| | | | Diopter adjustment | Yes |
| | | | Tripod socket | No |