

SEKONIC®

L-398A



Specifications			SEKONIC L-398A		
Light receivingment	Incident light	Swivel head	Horizontal (300 degrees)		
		Lumidisc	Removable		
	Reflected light	Switching incident/reflected	Removable		
		Light receiving angle	30(Lumigrad)		
		Viewfinder(Optional)	No		
	Flash light	Multiple flash mode	No		
		Cordless/cord-in mode	No		
Rado triggering		No			
Measuring Range(ISO100)	Ambient	Incident	EV	4 to 17	
		Reflected	EV	9 to 17	
		Illuminance	LUX	No	
			FC(FootNoCandle)	No	
	Luminance	Cd/m2	No		
		FL(FootNoLambert)	No		
	Flash	Incident	F	No	
Reflected		F	No		
Display	ISO Sensitivity		ISO	6 to 12,000	
			ISO 2	No	
	Ambient	Aperture	Digital	No	
			Step	1/3AV	
				Analog dot scale	No
				Step	No
			Shutter speed	Digital	No
			Step	No	
			Cine speed	Digital	No
	Flash	Aperture	Digital	No	
Shutter speed		Digital	No		
Setting Range	Film		ISO	No	
			Step	No	
			ISO 2	No	
			Step	No	
	Ambient	Aperture	F	No	
			Step	No	
		Shutter speed	T	No	
			Step	No	
			Cine	frame per second	8, 18, 24, 64, 128
	Flash	Shutter speed	T	No	
Step			No		
Operation function			Multiple cumulative	No	
			Average	No	
			Flash Analyzing	No	
			Memory	No	
			Memory clear	No	
			Battery check	No	
			Auto power off	No	
			Under/Over exposure display	No	
			Exposure Warning Indicator	No	
			Exposure compensation	No	
			Calibration compensation	No	
			Synchro terminal	No	
			LCD backlight	No	
			Water resistance	No	
			Switching incident/reflected	No	
			Retractable lumisphere	No	
			Running (setting) lock	No	
			Set/change dial (jog wheel)	No	
			Diopter adjustment	No	
			Tripod socket	No	